



Supports:  
PD 3.0 & QC 3.0



Charge up to 4  
devices



Compact  
design



Eco friendly  
packaging

## Unleash the Power

Verbatim's 30W USB Wall Charger consolidates multiple chargers into one, combining one USB-C PD 20W ports, one USB-C 18W QC 3.0 port and two USB-A 10W ports in a light, palm sized design.

Ideal for the office, home or travelling to power your tablet, smartphone, gaming devices, and more.

The USB Wall Charger is made with high-quality, flame-resistant materials and features four safety protection systems to ensure your safety while charging.

# USB Wall Charger 30W

1x USB-C® PD 20W / 1x USB-A QC 3.0 / 2x USB-A 10W

General Information					
Material	PC+ABS fireproof				
Colour	Black (49700) / White (49701)				
Input Plug Formats	EU (Type C)				
Supported devices	iPhone, iPad, Smartphones, Tablet PCs, MP3/MP4 players, etc.				
Power					
Input	100-240 V AC 50/60Hz 0.5 A (Max)				
Total Output	30W Max				
Single Port Output					
USB-C PD 3.0	5V=3A, 9V=2.22A, 12V=1.67A (20W max.)				
USB-A1 QC 3.0	5V=3A, 9V=2A, 12V=3A (18W max.)				
USB-A2	5V=2A (10W max.)				
USB-A3	5V=2A (10W max.)				
Multiport Output		USB-C PD 3.0	USB-A1 QC 3.0	USB-A2	USB-A3
USB-C1+USB-A1		7.5W	7.5W	-	-
USB-C1+USB-A2		20W	-	10W	-
USB-C1+USB-A3		18W	-	-	10W
USB-A1+USB-A2		-	18W	10W	-
USB-A1+USB-A3		-	18W	-	10W
USB-A2+USB-A3		-	-	5W	5W
USB-C+USB-A1+USB-A2		7.5W	7.5W	10W	-
USB-C+USB-A1+USB-A3		7.5W	7.5W	-	10W
USB-C+USB-A2+USB-A3		20W	-	5W	5W
USB-A1+USB-A2+USB-A3		-	18W	5W	5W
USB-C+USB-A1+USB-A2+USB-A3		7.5W	7.5W	5W	5W



**USB-A 2/3 Output:**  
Max 10W (when used alone)

**USB-A1 QC 3.0 Output:**  
Max 18W (when used alone)

**USB-C PD 3.0 Output:**  
Max 20W (when used alone)

# USB Wall Charger 30W

1x USB-C® PD 20W / 1x USB-A QC 3.0 / 2x USB-A 10W



Other Features	
Compliance	Electromagnetic Compatibility (2014/30/EC), Low Voltage Directive (2014/35/EC) and General Product Safety Directive (2001/95/EC). EN 55032:2015+A11:2020+A1:2020 EN 55035:2017+A11:2020 EN IEC 61000-3-2:2019+A1:2021 EN 61000-3-3:2013+A1:2019+A2:2021 EN IEC 62368-1:2020+A11:2020
ROHS compliance	Yes
Output short circuit protect	On short circuit protection situation, will stop charging to protect devices
Over-voltage protection	Yes
Over-current protection	Yes
Over-temperature protection	Yes

Storage and Operating Conditions	
Operating Temperature	-10°C ~ +40°C
Storage Temperature	-20°C ~ +80°C
Operating Humidity	5%(0°C) ~ 90%(40°C)RH

PN	Description	Bar Code	EAN128 Code	EAN14 Code
49700	Verbatim CHR-30EU1 USB Charger 30W with 1x USB-C® PD 20W / 1x USB-A QC 3.0 / 2x USB-A 10W Black (EU)	023942497004	(02)00023942497004(37)10(91)892 (02)00023942497004(37)40(91)892	20023942497008 50023942497009
49701	Verbatim CHR-30EU2 USB Charger 30W with 1x USB-C® PD 20W / 1x USB-A QC 3.0 / 2x USB-A 10W White (EU)	023942497011	(02)00023942497011(37)10(91)892 (02)00023942497011(37)40(91)892	20023942497015 50023942497016

Logistic Information	
Product Dimensions L x W x H	91.2 x 27.5 x 45.7mm
Product Weight	66 grams
Units per Pack	1
Pack Dimensions L x W x H	75 x 30 x 119mm
Pack Weight	106 grams (approx)
Units per Inner Carton	10
Inner Carton Dimensions L x W x H	255 x 170 x 95mm
Inner Carton Weight	1 200 grams
Units per Outer Carton	40
Outer Carton Dimensions L x W x H	375 x 280 x 230mm
Master Cartons Weight	5 600
Master Cartons per Layer	12
Layers per Pallet	4
Units per Pallet	1 920

# USB Wall Charger 30W

1x USB-C® PD 20W / 1x USB-A QC 3.0 / 2x USB-A 10W

**Verbatim**<sup>™</sup>

Technology you can trust



49700 Front



49700 Back Angled



49700 EU Plug



49700 Back Angled 2



49701 Packaging flat



49701 Packaging 3D



49701 Front



49701 Back Angled



49701 EU Plug



49701 Back Angled 2



49701 Packaging flat



49701 Packaging 3D

## Pack Contents:

- USB Wall Charger
- Quick Start Guide

## Warning

- INDOOR USE ONLY

For more information, please contact your key account manager

Publication date: 17-11-2023  
© 2023 Verbatim. All rights reserved.  
All brand names are registered trademarks of their respective owners.  
Unauthorized use strictly prohibited.  
Specifications are subject to change without prior notice.