

## Heat shrink butt crimp connectors $\varnothing$ 0.3 ... 6 mm<sup>2</sup> bulk set



This bulk set is especially suitable for hobbyists, craftsmen, field service, service workshops, electronics technicians and laboratory needs. The hot-melt inner adhesive provides a waterproof seal when properly overlapped. Optimal for repairing or connecting cables and conductors (lawn mower tracer cables, signal cables, etc.), service, manufacturing or hobby. Application is very simple: strip cable and insert on both sides until stripped cable ends overlap. Crimp with crimping pliers and then activate the heat shrink tubing in the respective temperature range - ideally with a heat gun. Waterproof, UL- REACH and RoHS compliant.

**Technical data:** Shrink ratio: 3:1 • IP class: IP67 • Temp. range: -55 ... 125 °C • Shrink temp.: 80 ... 130 °C • Voltage resistance: 600 V.

Part No.	Description	Color	Cross section	Diameter	Current max.	EAN / GTIN	Content
22C465	Heat shrink butt crimp connector 6,9 mm yellow 80 pcs	Yellow	4 ... 6 mm <sup>2</sup>	6.9 mm	48 A	4260732281559	80 pcs
22C466	Heat shrink butt crimp connector 5,7 mm blue 150 pcs	Blue	1.5 ... 2.5 mm <sup>2</sup>	5.7 mm	27 A	4260732281566	150 pcs
22C467	Heat shrink butt crimp connector 4,7 mm red 150 pcs	Red	0.5 ... 1.5 mm <sup>2</sup>	4.7 mm	19 A	4260732281573	150 pcs
22C468	Heat shrink butt crimp connector 6 mm black 80 pcs	Black	2.5 ... 4 mm <sup>2</sup>	6 mm	35 A	4260732281580	80 pcs
22C469	Heat shrink butt crimp connector 4 mm white 150 pcs	White	0.3 ... 0.5 mm <sup>2</sup>	4 mm	9 A	4260732281597	150 pcs

Connection only by qualified electricians. We assume no liability or warranty in case of incorrect application.